



COATING AREA CHART		
	PER FOOT OF SHEET	PER SQUARE FOOT OF WALL
SINGLE SHEET- DIPPED	7.86 SQ.FT.	2.43 SQ.FT.
SINGLE SHEET- SPRAYED	7.54 SQ.FT.	2.33 SQ.FT.
PAIRED SHEETS- SPRAYED	6.67 SQ.FT.	2.06 SQ.FT.
INSTALLED SHEETS- SPRAYED	6.11 SQ.FT.	1.89 SQ.FT.

COMPUTED PROPERTIES, AS DESIGNED
 AREA PER PILE - 18.980 SQ. IN.
 AREA PER FOOT OF WALL - 5.867 SQ. IN.
 LAYING WIDTH - 38.817 IN. = 3.23475 FT.
 WEIGHT PER FOOT OF PILE - 64.597 LBS.
 WEIGHT PER SQ. FOOT OF WALL - 19.969 LBS.
 WALL DEPTH - 3.693 IN.
 MATERIAL THICKNESS - 0.406 IN.
 MOMENT OF INERTIA PER PILE - 5.583 IN.⁴
 MOMENT OF INERTIA PER FOOT OF WALL - 1.726 IN.⁴
 SECTION MODULUS PER PILE - 2.798 IN.³
 SECTION MODULUS PER FOOT OF WALL - 0.865 IN.³
 SHEET SECTION PERIMETER - 94.312 IN.
 C/G TO OUTER FIBER - Y = 1.995 IN.

ROLL FROM 0.406" STRIP APPROX. 46.75" WIDE

DRAWING		MSZ 406-12 STATION 10	
PROJECT		SHORELINE STEEL SUPPLY, INC.	
SCALE	FULL SIZE	DRAWING DATE	29 APRIL 2010
DRAWN BY	J.C.B.	LAST REV. DATE	1 DEC 2012
GENERAL MARINE SERVICE CORPORATION		10-0500	
25504 ARDMORE PARK DRIVE		DRAWING NUMBER	
ST. CLAIR SHORES, MI 48081-0011			
586-777-0045			